



Element Materials Technology
2 Pheasant Run
Newtown, PA
18940-1819 USA

P 215 579 7500
F 215 579 7591
T 888 786 7555
info.newtown@element.com
element.com

Contact: Bruce W. Herman
Vinylast
1830 Swarthmore Avenue
LAKEWOOD, NJ 08701

TEST CERTIFICATE — EAR-CONTROLLED DATA

Date: 12/16/2013
P.O. No.: PO10988
W/O No.: VIN028-10-28-15850-1

DESCRIPTION

Double Zinc Shore Coated Test Sample

Salt Spray Results

Requirements: Report only

One sample supported or suspended between 15° and 30° was tested in a salt chamber using a 5% salt solution at 95°F for a total of 1000 hours, tested in accordance with ASTM-B117-11.

Time
24-1000 Hours

Results
no attack

This document contains technical data whose export and re-export/ retransfer is subject to control by the U.S. Department of Commerce under the Export Administration Act and the Export Administration Regulations. The Department of Commerce's prior written approval may be required for the export or re-export/retransfer of such technical data to any foreign person, foreign entity or foreign organization whether in the United States or abroad.

Respectfully submitted

Peggy Wolfe
Quality Administrator

Information and statements in this report are derived from material, information and/or specifications furnished by the client and exclude any expressed or implied warranties as to the fitness of the material tested or analyzed for any particular purpose or use. The testing reported on this certification has been performed in accordance with QAM 4th Edition Rev. 2 Dated 12/06/2011 and related procedures. All testing has been performed in accordance with the latest revision of the applicable published test method in effect at the time of testing, unless otherwise stated. This report shall not be reproduced except in full, without written approval of this laboratory. The recording of false, fictitious, or fraudulent statements or entries on this document may be punished as a felony under Federal Statutes including Federal Law Title 18, Chapter 47. Sample remnants are held for a minimum of 30 days following issuance of test results, at which point they will be discarded unless notified in writing by the client.

ALL TESTING PERFORMED IN A MERCURY-FREE ENVIRONMENT